

## TECHNICAL DATA

<b>A</b>	<b>Max. Working Height</b>	<b>17'6"</b>
<b>B</b>	<b>Max Platform Height (Upright fully extended)</b>	<b>11'</b>
<b>C</b>	<b>Height Stowed</b>	<b>56.7"</b>
<b>D</b>	<b>Length Stowed</b>	<b>57"</b>
<b>E</b>	<b>Width</b>	<b>31.8"</b>
<b>F</b>	<b>Entry Step</b>	<b>14"</b>
<b>Occupants</b>		<b>1</b>
<b>Unit Gross Weight (Unoccupied)</b>		<b>1,499 lbs</b>
<b>Drive Speed Stowed</b>		<b>3.54 mph</b>
<b>Drive Speed Raised</b>		<b>0.54 mph</b>
<b>Gradeability</b>		<b>35%</b>
<b>Raise/Lower Speed</b>		<b>18/14 sec</b>
<b>Driving System</b>		<b>Two-Handed Proportional</b>
<b>Tires</b>		<b>Full Non Marking</b>
<b>Tilt Sensor</b>		<b>Standard</b>
<b>Inside Turning Radius</b>		<b>Zero</b>
<b>Outside Turning Radius</b>		<b>57"</b>

## CAPACITIES


<b>G</b>	<b>Operator's Bay Capacity</b>	<b>287 lbs</b>
<b>H</b>	<b>Materials Tray Capacity</b>	<b>198.41 lbs</b>
<b>I</b>	<b>Transport Hood Tray Capacity</b>	<b>249.12 lbs</b>
<b>J</b>	<b>Trailer Tow Capacity</b>	<b>440 lbs</b>

## POWER

<b>Batteries</b>	<b>4 - 6V 245AH</b>
<b>Power</b>	<b>24 V c.c.</b>
<b>Load Network Power</b>	<b>220 V c.a.</b>
<b>Duty Cycle-Drive (On one charge)</b>	<b>18.5 Miles</b>



Acceleration of forward/backward movement is proportional and positioned near the basket raising and lowering button, to enable these movements even during forward movement. All systems are operable without having to move the hand from the accelerator, for maximum operator comfort.



## ZERO Inside Turning Radius and 57" Outside Turning Radius

Material tray is electrically operated by a button in the upper control box.

The ISP-11 features an anchoring point on the back of the chassis where a hook can be fastened to a tow trailer carrying up to 440 lbs.

Loading platform at maximum height corresponds to the column height. It is very easy to place even heavy packages using the column as the setting base and letting it slide onto the material tray.

The revolutionary raising system already created by Bravi Platforms for its mobile platform models is a radical change for this business segment. The column in special extruded aluminum alloy is completely without any need of maintenance.

- No more chains to be inspected every year
- No more grease on the mast
- No maintenance required
- Futuristic canopies are ergonomically designed, made of resilient carbon.
- Completely sealed to enhance protection against shocks and damages caused by debris falling from above.




Safety position with double sensor pedal and left hand sensor allow activation of the functions. These safety devices serve to guarantee the stable position of the operator, with both hands on the controls before these become activated.

## AEUP® Platinum Warranty™

The **BEST** warranty in the industry:  
**10 years** on the mast and cylinder  
**5 years** on all components  
**1 year** on batteries, not prorated

## Options:

- Holder for Bar Code Scanner
- Audible alarm for gate when platform is elevated and open
- Automatic locking system for gate when platform is elevated
- Updated Steering Actuators



**More than 18.5 miles on one battery charge!**

distributed by:



**Absolute E-Z Up® Inc.**  
 Charleston, SC 29492  
 office: 843-388-2556  
 fax: 843-388-2558  
 e-mail: salesdept@absolute-zup.com  
 web: www.absolute-zup.com

Manufactured by



© September 2017 Absolute E-Z Up® Inc.  
 Specifications subject to change without notice.  
 Photos and drawings are for illustrative purposes.

