



TECHNICAL DATA

AEUP ISP-11

JLG 10 MSP

JLG 15 MSP

Max Working Height	17'6"	16'	21'3"
Max Platform Height	11'	10'	15'3"
Height Stowed	56.7"	56"	76"
Length Stowed	57"	60"	53.5"
Width	31.8"	33"	29.5"
Platform Entrance Height	14"	13"	16"
Occupants	1	1	1
Unit Gross Weight	1499 Lbs	1100	2425
Drive Speed Stowed	4. mph	3.5 mph	3.5 mph
Drive Speed Raised	0.54 mph		
Max Gradeability	35%	30%	30%
Raise/Lower Speed	18/14 sec	?	?
Turning Radius Outside	57"	?	?
Turning Radius Inside	ZERO	ZERO	47.5"
Pothole Protection	not needed	Has--automatic/manual	Has--automatic/manual
Driving System	Electric Direct Drive Wheel Motors(2) Proportional forward/reverse accelerator	Electric Direct Drive Wheel Motors (2) One-Handed Proportional Joystick	Electric Direct Drive Wheel Motors (2) One-handed Proportional
Operation-drive/lift/steer	3 functions simultaneously	2 functions	2 functions
Tire	Solid Rubber Non-Marking	Solid Rubber Non-Marking	Solid Rubber Non-Marking
Tilt Sensor Cut Out	Standard	Standard	Standard
Material Tray	Powered-electric	Manual	Manual
Trailer Tow Capacity	440 lbs	none	none

CAPACITIES

Operator's Bay Capacity	286 Lbs	350 lbs	
Transport Hood Tray Capacity	248.9 Lbs	250 lbs	500 lbs total
Materials Tray Capacity	198.2 Lbs	250 lbs	500 lbs w/ deck extension

POWER

Batteries	4-6V 245 amp hr	4-210 amp hr AGM	2-100 amp hr AGM
Power	24 volt	24 V c.c.	24 V c.c.
Travel Distance-one charge	18.6 Miles		

WARRANTY	10 Year - Mast/Cylinder 5 Year - every other component 1 Year Battery - not pro-rated	5 Year 1 Year	5 Year 1 Year
-----------------	---	------------------	------------------

Inspection			
Inspection of cable or chains	Doesn't have-not needed	Required	Required

Maintenance			
Adjustment or replacement of cables or chains	NA	Required	Required
Lubrication of cables or chains	NA	Required	Required